





Standard Fibreglass Flagpole System



Fiberglass Flagpoles



1 2 3 4

Betong concrete

300-400 mm

A




Mark - Ground

M	6-8 m	9 m	10 m	12 m
A= mm	300	300	400	400
B= mm	800	900	1000	1200



B

2-300 mm

A




Hinge and foundation data




Product Specifications

Fibreglass flagpole		6 meter	7 meter	8 meter	9 meter	10 meter	11 meter	12 meter
Complete weight with steelwork		23kg	25kg	27kg	29kg	37kg	40kg	43kg
Top diameter of pole	②	65mm	65mm	65mm	65mm	65mm	65mm	65mm
Height to cleate	③	1500mm	1500mm	1500mm	1500mm	1500mm	1500mm	1500mm
Length of steel pipe	④	660mm	660mm	660mm	660mm	660mm	660mm	660mm
Thickness of steel pipe	④	4.0mm	4.0mm	4.0mm	4.0mm	5.8mm	5.8mm	5.8mm
Diameter of steel pipe	④	102mm	102mm	102mm	102mm	121mm	121mm	121mm
Butt diameter of steel pipe	⑤	120mm	120mm	120mm	120mm	140mm	140mm	140mm
Fiberglass thickness+0.5mm	⑤	3.0mm	3.0mm	3.0mm	3.0mm	3.5mm	3.5mm	3.5mm
Depth of ground foundation	⑥	800mm	800mm	800mm	900mm	1000mm	1100mm	1200mm
Diameter of ground foundation	⑦	300mm	300mm	300mm	300mm	400mm	400mm	400mm
Hole diameter for rock install	⑨	35mm	35mm	35mm	35mm	35mm	35mm	35mm
Depth of hole for rock install.	⑧	300mm	300mm	300mm	400mm	400mm	400mm	400mm
Recommended Flagsize		150cm	200cm	200cm	240cm	240cm	300cm	300cm

Flagpole with Rotating Flag Arm Instructions



Conecting a Flag to Internal Halyard



Connecting the top of the flag:


1. Tie a loop in the flagpole rope that is coming out of the top of the flagpole.
2. Push the toggle that is in the top of the flag through this loop on the flagpole rope.

Conecting the bottom of the flag:

1. Tie a loop in the flag rope that is on the bottom of the flag.
2. Clip flag weight onto this loop.
3. Hoist the flag upto the top of the flagpole.

Flag Size Guide - Practical Recommendations

Union Flag Company • Guide to pairing flag sizes with common pole heights



The quick rule

Use one yard of flag fly for roughly every 10 feet of pole height. For example, a 6 m pole (about 20 ft) suits a 2-yard flag at 183 x 91 cm. This rule keeps the proportions balanced and wind load sensible.


Recommended sizes for Ground Mounted Flagpole height (landscape flags)

Pole height	Recommended yard size	Metric size
4 m	1½ yard	135cm x 68cm
5 m	2 yard	183cm x 91cm
6 m	2 yard	183cm x 91cm
7 m	2½ yard	229cm x 114cm
8 m	2½ yard or 3 yard	229cm x 114cm or 274cm x 137cm
9 m	3 yard	274cm x 137cm
10 m	3 yard or 4 yard	274cm x 137cm or 366cm x 183cm

Tip: if the site is exposed or the pole is older, choose the smaller size to reduce strain on the halyard, cleat and truckhead.

Practical notes


- Choose the smaller size for high-wind locations or heritage poles to reduce stress.
- Flying multiple flags on one pole? Step down the size for the lower position.



Recommended sizes for Wall-mounted short poles (angled)

Pole height	Recommended yard size	Metric size
1.5 m	1½ yard	137cm x 68cm
2 m	1½ yard - 2 yard	137cm x 68cm or 183cm x 91cm
2.5 m	2 yard	183cm x 91cm
3 m	2 yard - 2½ yard	183cm x 91cm or 229cm x 114cm

Tip: if the site is exposed or the pole is older, choose the smaller size to reduce strain on the halyard, cleat and truckhead.



Recommended sizes for Show Home Landscape or banner-style flags (rotating-arm setups)

Pole height	Recommended yard size	Metric size
5 m – With Rotating Arm	-	225cm x 91cm (single-sided)
6 m – With Rotating Arm	-	250cm x 91cm (single-sided)
7 m – With Rotating Arm	-	300cm x 100cm (single-sided)
5 m	2 yard	183cm x 91cm
6 m	2 yard	183cm x 91cm
7 m	2½ yard	229cm x 114cm

Tip: if the site is exposed choose the smaller size to reduce strain on the flagpole, rotating arm, halyard, cleat and truckhead.